

## DHS Series

Submersible Pumps  
Drainage & Vortex Submersibles



### Application

- Submersible installation
- Stormwater transfer
- Waste / Greywater transfer
- Dewatering

### Features

- Stainless steel motor and pump shaft
- Vortex impeller
- Mechanical seal with back-up lip seal
- Soft solids handling up to 30mm
- 10m power cable
- Corrosion resistant body and base

### Construction

- Pump body: Technopolymer
- Motor shaft: Stainless steel AISI 304
- Impeller: Technopolymer
- Mechanical seal: Ceramic – Graphite
- Motor IP68
- Electric power cable HO5RN 10m with 3 pin

### Dimensions

Model	H (mm)	L (mm)	DNI	G.W (kg)
DHS400	330	210	32F	4.5

### Technical Data



Model	Power (P2) (kW)	Amps (A)	Max. FLOW (L/min)	Max. HEAD (m)	Cable (m)	Pump Style	Outlet	Solids Passage (mm)
DHS400	0.40	2.2	156	7	10	Vortex	1-1/4"	30



DHS400  
- Vortex



### Performance



### Application

- Submersible installation
- Stormwater transfer
- Waste / Greywater transfer
- Dewatering



### Features

- Stainless steel motor and pump shaft
- Vortex impeller
- Mechanical seal with back-up lip seal
- Soft solids handling up to 30mm
- 10m power cable
- Corrosion resistant body and base

### Construction

- Pump body: Stainless steel AISI 304
- Motor shaft: Stainless steel AISI 304
- Impeller: Technopolymer
- Mechanical seal: Ceramic – Graphite
- Motor IP68
- Electric power cable HO5RN 10m with 3 pin

### Performance



### Dimensions

Model	H (mm)	L (mm)	DNI	G.W (kg)
DHS750	290	235	40F	6.9

### Technical Data

Model	Power (P2) (kW)	Amps (A)	Max. FLOW (L/min)	Max. HEAD (m)	Cable (m)	Pump Style	Outlet	Solids Passage (mm)
DHS750	0.75	3.2	200	9	10	Vortex	1-1/2"	30

## Commercial Plumbing & Fire Supplies

### Site Address

6A Kelly Court,  
Springvale, VIC 3171

### Postal Address

6A Kelly Court,  
Springvale, VIC 3171

### Contact Details

P: 03 9791 7500  
E: sale@cpfs.net.au

