



Cooling, Heating, Air Purifying & Self-Cleaning at your Fingertips.



Soave R32 Wall Mounted Wi-Fi Reverse Cycle Air Conditioner



Smart Control with Wi-Fi App and Voice Control.



Ergonomic, backlit wireless remote controller for ease of use.



Ion Generation Air Purifying technology. Deactivates bacteria and viruses.



UV Sterilisation technology eliminates microorganisms inside the indoor unit.



Self-Cleaning technology for clean air all year round.




Sustainable, natural refrigerant R32 with GWP=675.



Industry leading cooling with **6.5 Energy Star Rating** for 2.6kW model.



Gentle Cooling with no direct drafts for greater comfort.



Turbo Cooling for a rapid relief at your choice.



Built for all Australian Climates. Operating Ambient from -15°C to +50°C.



Designed for **Easy Installation** and optimised maintenance experience.



5-Year Warranty for peace of mind.

Contact Details:

P: 03 9791 7500

E: Sales@ecoheat.au

E: Sales@cpfs.net.au

Soave R32 Wall Mounted Wi-Fi Reverse Cycle Air Conditioner

SmartLife - SmartHome App



Note: Images are for illustration purposes only. Actual sizes may vary depending on capacity.

Model Class			2.1	2.6	3.5	5.2	7.2	8.2
Rated Cooling Capacity (Min - Max)		kW	2.15 (0.60-2.80)	2.64 (0.80-3.70)	3.53 (0.90-4.20)	5.30 (1.00-5.60)	7.20 (1.50-7.50)	8.20 (1.50-8.50)
EER/AEER			4.13 / 4.03	4.71 / 4.60	4.06 / 4.00	4.08 / 4.04	3.44 / 3.40	3.44 / 3.41
Rated Heating Capacity (Min - Max)		kW	2.10 (0.60-3.50)	3.30 (0.60-4.40)	3.65 (0.80-5.20)	5.30 (1.00-5.80)	7.30 (1.50-7.80)	8.40 (1.50-8.50)
COP/ACOP			4.77 / 4.63	4.43 / 4.35	4.29 / 4.24	4.34 / 4.30	3.99 / 3.96	3.65 / 3.63
Star Rating	Hot Climate	Cooling	4.5	6.5	5.5	4.5	3.5	3.5
		Heating	3.0	3.5	3.5	3.5	3.5	3.5
	Average Climate	Cooling	3.5	5.0	4.5	4.0	3.0	3.0
		Heating	3.0	3.0	3.0	3.0	3.0	2.5
	Cold Climate	Cooling	3.5	5.0	4.5	4.0	3.5	3.5
		Heating	2.5	2.5	2.5	2.5	2.0	2.0
Sound Pressure Level	Indoor (Min/ Med/Max)	dB(A)	20 / 29 / 40	20 / 30 / 43	20 / 30 / 43	30 / 40 / 49	28 / 37 / 49	31 / 41 / 50
	Outdoor (Min/ Med/Max)	dB(A)	52	53	54	59	59	60
Power Supply			220 -240V / 1 Phase / 50Hz					
Unit Weight	Net kg	Indoor	8.0	9.0	9.0	13.0	14.0	14.0
		Outdoor	21.0	23.0	24.0	37.0	38.5	45.0
Unit Dimensions	Net (HxWxD) m	Indoor	275 x 788 x 192	306 x 820 x 195	306 x 820 x 195	332 x 1097 x 222	332 x 1097 x 222	332 x 1097 x 222
		Outdoor	498 x 787 x 290	549 x 795 x 305	549 x 795 x 305	699 x 927 x 380	699 x 927 x 380	803 x 967 x 421
Refrigerant Pipe Diameter	Liquid Pipe	mm/(inch)	Ø6.25 (1/4")	Ø6.25 (1/4")	Ø6.25 (1/4")	Ø6.25 (1/4")	Ø6.25 (1/4")	Ø6.25 (1/4")
	Gas Pipe	mm/(inch)	Ø9.52 (3/8")	Ø9.52 (3/8")	Ø9.52 (3/8")	Ø12.70 (1/2")	Ø12.70 (1/2")	Ø12.70 (1/2")
Refrigerant	Type		R32					
Pipe Length (Min- Max)	m		3 - 15					
Max Elevation Pipe Length	m		10	10	10	15	15	15
Outdoor Operating Range	Cooling		15°C - 50°C					
	Heating		-15°C - 24°C					

Note:

- (1) Cooling capacity: Indoor temperature 27°C DB/ 19.5°C WB, Outdoor temperature 35°C DB/24°C WB.
- (2) Heating capacity: Indoor temperature 20°C DB, Outdoor temperature 7°C DB/ 6°C WB.

Why Choose Maxa Soave R32 Wi-Fi Wall Mounted Reverse Cycle Air Conditioners?

The Maxa Soave combines sleek, modern aesthetics with high performance, catering to the demands for energy efficiency and whisper-quiet operation.

Maxa Soave is equipped with an air purifying device, UV sterilisation device, and self-cleaning technology. These features, coupled with the Turbo Cooling and Gentle Cooling functions, provide clean and comfortable air throughout the year.

Contact Details:
P: 03 9791 7500
E: Sales@ecoheat.au
E: Sales@cpfs.net.au